


Humidity / Temperature Monitors 800016, 800015, 800027

Simultaneously monitor both temperature and humidity on a large 3-3/16 x 2 1/2" display. Useful in incubators, refrigerators, desiccators, environmental chambers, labs, clean rooms, stock rooms, warehouses, factories, greenhouses, and outdoors. Recall min/max temperature & humidity readings over any time period. °C and °F selectable, stand or wall mount. Come with 1 AAA battery which lasts a full year. N.I.S.T. traceable certificate of compliance available.

Model 800016 reads temperature and RH on a dual display. Model 800015 adds an external temperature sensor on a remote probe and features a triple display of all 3 parameters. Model 800027 adds internal and external RH displaying all four parameters simultaneously.

DIM: 4 1/4" x 4" x 7/8" (110 x 102 x 20 mm). WEIGHT: 5 oz (142 g).



		800016	800015	800027
Range	Temp In	0 ~ 50°C (32 ~ 122°F)		
	Temp Out		-50 ~ 70°C (-58 ~ 158°F)	
	RH	10 ~ 99%		
Resolution	Temp	0.1°C		
	RH	1%		
Accuracy	Temp	±1°C (±2°F)		
	RH	±5%		
Internal Temp		✓	✓	✓
Internal RH		✓	✓	✓
External Temp			✓	✓
External RH				✓

No.	Description
-----	-------------

- | | |
|--------|--|
| 800016 | Humidity/Temperature Monitor |
| 800015 | Humidity/Temperature Monitor with Remote Temperature |
| 800027 | In/Out - Humidity Temperature Monitor |



Eastern Energy Co., Ltd.
40/4 Vitoondumri Rd., Banbueng
Banbueng, Chonburi, Thailand

Tel: 66-3844-6117
sale@ete.co.th
www.eastern-energy.com