



Model 6605



EMC & LVD  
EN: 61326  
EN: 61010-1,  
EN: 62010-02-031



**Wide Range Measurement up to 5kV with Insulation Resistance to 60GΩ**

Specifications						
Function	Insulation resistance				Voltage	Resistance
Range	500V	1000V	2500V	5000V	AC/DCV	
Measuring range (Auto ranging)	0~6.000MΩ 6~60.00MΩ 60~600.0MΩ 600~6000MΩ	0~6.000MΩ 6~60.00MΩ 60~600.0MΩ 600~6000MΩ	0~60.00MΩ 60~600.0MΩ 0.6~6.000GΩ 6~60.00GΩ	60~60.00MΩ 60~600.0MΩ 0.6~6.000GΩ 6~60.00GΩ	0~600.0V (50~1kHz)	0~600.0Ω 600~6000Ω
Accuracy	±5%rdg ±3dgt ; ±20% (>6GΩ or more)				±1.5%rdg ±5dgt	±1.5%rdg ±10dgt
Short Circuit Current	1.3mA approx				-	
Rated test Current (at load Resistance)	1mA-1.2mA 0.5MΩ	1mA-1.2mA 1MΩ	1mA-1.2mA 2.5MΩ	1mA-1.2mA 5MΩ	-	
Open circuit voltage	500VDC/+20%-0%	1000VDC/+20%-0%	2500VDC/+20%-0%	5000VDC/+20%-0%	-	
Continuity check	Buzzer sounds at 50Ω					
Display	6000 Counts					
Current consumption	About 1000mA (During measurement)				25mA approx.	
Withstand Voltage	5320V AC for 5 seconds					
Safety standard	IEC 61010-1 CAT IV 600V Pollution Degree 2					
Power supply	DC12V : R14 x 8					
Dimensions	198 ( L ) x 148 ( W ) x 86 ( D ) mm					
Weight	1438g approx.					
Accessories	Test leads, Instruction Manual and 120V/250V AC adaptor					