CO² / Temperature / Humidity Monitor



TM-185A Temperature / Humidity Monitor TM-187A CO² Monitor

NEW

Features

- Complete environmental monitoring and alarm solution.
- Wall-Mounted LED type for easy reading.
- Alarm set for CO2 and Temperature and Humidity.
- USB Datalogging Capacity 65,000 records.
- Real-time data display.

Applications

- Warehouses.
- Chambers / incubator.
- Laboratories.
- Electronics manufacturing.
- Computer rooms.
- Clean rooms.
- Refrigerators.
- Defense.
- Hospitals blood / Tissue banks.
- Other Critical areas.







TM-185A







Technical parameters:

Sampling time	1 time / second
Interval time	1s~24hrs
Output interface	RS485/RS-232/USB With a time of three options
Analog output	4-20mA Output(RL≦250Ω)
Dry contact (Relay Switch)	Contact : Max. 1A @30Vdc Resistive load
Power	24Vac / Vdc ±20%(5060Hz) and 9-15V Adaptor
Power consumption	6W@ 24Vdc

Temperature:

Туре	Diode
Range	-20°C~70°C / -4°F~158°F
Accuracy	±1.0°C (5~60°C)other ±2°C
Resolution	0.1°C / 0.1F (0~35°C / 32°F~95°F); 1°C / 1°F(over 100°C/°F or below -10°C/°F)
Response Time	Typ.1 second

CO2 (TM-187A only):

Туре	Non-dispersive infrared(NDIR)				
Range	1 to 9999ppm				
Accuracy	±5% of reading or ±70ppm. (0-2000ppm, others out of scale range)				
Resolution	±1ppm				
Response Time	Typ. 2 minutes by 90%				

Relative Humidity:

Туре	Capacitive					
Range	5-95%					
Accuracy	±5.0%RH(20~80%); ±8.0%RH(<20%,>80%)					
Resolution	0.1%					
Response Time	Typ. 4 seconds					

	CO ²	Humidity	Temp	65,000Record	Clock	RS-232	RS-485	RELAY *1	4 - 20mA
TM-185A		•	•	•	•	•	•	•	•
TM-187A	•	•	•	•	•	•	•	•	•